Key Features

| Ultra HD Resolution

| POWERFUL EMBEDDED SOC PLATFORM

| EMBEDDED LAN AND USB WIRELESS CONNECTIVITY

| VIEWBOARD ® CAST CONTENT SHARING SOFTWARE

| Remote Content Sharing from Anywhere



Product **Description**

The ViewSonic* CDE4312 is a 43" 4K Ultra HD large format wireless presentation display. With features including a razor-sharp resolution of 3840 x 2160, 230-nit high brightness, 178-degree ultra-wide viewing angles, 2 x 10W speakers, and wireless screen sharing, the CDE4312 transforms meeting rooms into a dynamic communications hub. The built-in ViewBoard* Cast screen sharing software* (along with the optional ViewSonic vCastSender app), and myViewBoard Display software, enables both on-site and online users to participate in conferences and simultaneously share content. Equipped with a 1.5GHz Quad-core embedded SoC processor, 2GB RAM, and 16GB of internal memory, the CDE4312 can play multimedia from internal storage or a USB flash drive 16 hours a day, seven days a week. And with remote configuration and content management system support, the ViewSonic CDE4312 is also suitable for a wide array of diverse signage applications.

*Chrome, Android, Windows, Mac OS, and iOS compliant









3840 x 2160

230 cd/m2 BRIGHTNESS

RESOLUTION

Audio:

Internal Speakers: 10W (x2)

Power:

100-240 VAC +/- 10% Wide Range, 50-60Hz +/-3 Hz Voltage:

Consumption (max): 85W Consumption (typical): 70W Stand-by: <0.5W

Controls:

On Screen Display: Picture, Screen, Audio, Time, Advanced Options, About

Operating Conditions:

32-104° F (0 - 40° C) Temperature:

20-80% Humidity (non-condensing):

Embedded Player:

Operating System: Android 9.0

CPU: Quad-core, 1.5GHz, MT9632/ARM Cortex-A53

16GB (eMMC)

GPU: Dual Core, G52MP2 2GB DDR4 Memory:

Storage: Display:

Static Contrast Ratio: 1,200:1

178° horizontal, 178° vertical Viewing Angles:

Resolution: 3840 x 2160 Colors: 1.07B Viewable Area (in.): 42.5 Dynamic Contrast Ratio: 5,000:1 Backlight Life (Hours): 30,000 Response Time (Typical GTG): 8ms Light Source: DLED

Panel Surface: Hard Coat - Anti-Glare, 2% Haze, 3H with anti-glare treatment

230 cd/m2

Aspect Ratio: 16:9

Weight (metric):

Brightness:

Gross (kg): 10.4 Net (kg): 6.6

Weight (imperial):

Net (lbs): 14.55 Gross (lbs): 22.93

Connector:

RCA Audio In(1), SPDIF Audio Out(1), USB 2.0(1), USB Type C(1), RS232 In(1), HDMI 2.0 In(2), VGA(1), Wi-Fi/Bluetooth Slot(1), Ethernet LAN (RJ45)(1), 3.5mm Audio Out(1)

Dimensions (metric) (WxHxD):

Packaging (mm): 1041 x 630 x 148 Physical (mm): 972.6 x 566.0 x 82.6

Dimensions (imperial) (WxHxD):

Packaging (in.): 40.98 x 24.8 x 5.83 Physical (in.): 38.3 x 22.3 x 3.3

Mount:

VESA Compatible: 200 x 200 mm

General:

Regulations: cULus, FCC, Energy Star, RoHS

PACKAGE CONTENTS: CDE4312, Remote control with batteries, Quick Start Guide, Power cable, HDMI

Cable, Wall Mount Screws and RS232 cable

Recycle/Disposal: Please dispose of in accordance with local, state or federal laws.

Warranty: Three-year limited warranty on parts, labor and backlight

UPC: 766907017632

Accessories:

NMP309-W, NMP589-W, NMP620-P10, NMP660, NMP760, VB-STND-001, VB-STND-005, VB-WIFI-001, VBS100-A, WMK-013, WMK-050

0