



Compact and Flexible 1-Chip DLP™ Projectors Deliver Elite Color Performance in Any Exhibition Space

■ Main Features

01 | Power to Impress with Accurate Colors

Deepen immersion in any environment with high brightness, rich color, and accurate white balance thanks to Quartet Color Harmonizer and 1-Chip DLP™ imaging technology.

02 | Easy to Install and Integrate

With versatile apps and functions, diverse optional lenses, support for 4K input signals^{*1}, and separate DIGITAL LINK and LAN terminals, these projectors reduce installation hassles with convenient flexibility.

03 | Reliable Even in Harsh Conditions

Engineered for 20,000 hours^{*2} of maintenance-free reliability with lasting brightness and color uniformity from the industry's leading dust-resistant optical engine.



Black Models



White Models

PT-RZ990 Series

	PT-RZ990	PT-RZ890	PT-RZ790	PT-RZ690
	PT-RZ990L ^{*3}	PT-RZ890L ^{*3}	PT-RZ790L ^{*3}	PT-RZ690L ^{*3}
Light Output	9,400 lm ^{*4} / 10,000 lm (Center) ^{*5}	8,500 lm ^{*4} / 8,800 lm (Center) ^{*5}	7,000 lm ^{*4} / 7,200 lm (Center) ^{*5}	6,000 lm ^{*4} / 6,200 lm (Center) ^{*5}
Resolution	WUXGA			

^{*1} Supports signals up to 4K/60p. 4K signals are converted to the projector's resolution (1920 x 1200 pixels) upon projection. Supported terminals: DIGITAL LINK/HDMI®. ^{*2} Around this time, light output will have decreased by approximately 50 %. IEC62087: 2008 Broadcast Contents, Normal Mode, Dynamic Contrast (3), temperature 30 °C (86 °F), elevation 700 m (2,297 ft) with 0.15 mg/m³ of airborne particulate matter. Panasonic recommends cleaning or checkup at point of purchase after about 20,000 hours. Light-source lifetime may be reduced depending on environmental conditions. Replacement of parts other than the light source may be required in a shorter period. Estimated maintenance time varies depending on environment. ^{*3} Model sold without a lens. ^{*4} Measurement, measuring conditions, and method of notation all comply with ISO/IEC 21118: 2020 international standards. Value is average of all products when shipped. ^{*5} Average light-output value of all shipped products measured at center of screen in Normal Mode.

Accurate Color Reproduction

Quartet Color Harmonizer is a color-wheel technology featuring an optimized optical design. It precisely modulates light-output to color requirements for pure white. With the color uniformity of DLP™ devices supporting seamless edge-blends, an immersive single- or multi-screen projection experience is assured.

Supports 4K Signal Input

The PT-RZ990 Series supports 4K input signals^{*1} and fits seamlessly into 4K-ready infrastructure. Separate LAN terminal for control frees DIGITAL LINK for high-bandwidth video over long cable runs up to 150 m (492 ft)^{*2}.

Flexible, Convenient Installation

Select from a family of 11 optional lenses including the new ET-DLE020 Ultra-Short-Throw Zoom Lens. Free Grid function corrects screen distortion without PC connection, while Smart Projector Control app expedites setup.



Scan the QR for details on Smart Projector Control.

20,000 Hours' Maintenance-free

Class-leading dust resistance, airtight optical block, and filterless cooling team with failover-protected dual-laser drive to extend maintenance-free projection to 20,000 hours^{*3}. Backup input-switching^{*4} adds extra insurance.

Other Features

- System Daylight View 3 and Detail Clarity Processor 3
- Dynamic Contrast Sync and Shutter Sync functions
- Multi-Unit Brightness and Color Control
- Supports Crestron®, AMX, and Extron® control
- Quick Start and Quick Off
- Geometry Manager Pro Software with optional expansion kits
- Multi Monitoring & Control Software with optional Early Warning Functions^{*5}

^{*1} 4K signals are converted to the projector's resolution (1920 x 1200 pixels) upon projection. ^{*2} CAT 5e cable or higher required. Transmission of up to 150 m (492 ft) for 1080/60p signals requires an optional ET-YFB200G DIGITAL LINK Switcher and the projector set to Long Reach Mode. 4K/60p signal transmission is supported for up to 50 m (164 ft). ^{*3} Around this time, light output will have decreased by approximately 50 %. IEC62087: 2008 Broadcast Contents, Normal Mode, Dynamic Contrast [3], temperature 30 °C (86 °F), elevation 700 m (2,297 ft) with 0.15 mg/m³ of airborne particulate matter. Panasonic recommends cleaning or checkup at point of purchase after about 20,000 hours. Light-source lifetime may be reduced depending on environmental conditions. Replacement of parts other than the light source may be required in a shorter period. Estimated maintenance time varies depending on environment. ^{*4} The combination of primary/secondary input terminals is fixed. Input switching occurs automatically when the signal to the primary input is disrupted or restored. Backup Input Setting is enabled only when the input signal to primary and secondary terminals is the same. ^{*5} A free 90-day trial of Early Warning Functions is available upon installation of free Multi Monitoring & Control Software Ver. 2.0 or later. Purchase a license and activate at PASS when trial period expires to continue using Early Warning Functions.

Specifications

Model	With supplied lens/Without lens	PT-RZ990/PT-RZ990L	PT-RZ890/PT-RZ890L	PT-RZ790/PT-RZ790L	PT-RZ690/PT-RZ690L
Projector type		1-Chip DLP™ projector			
DLP™ chip	Panel size	17.0 mm (0.67 in) diagonal (16:10 aspect ratio)			
	Number of pixels	2,304,000 (1920 x 1200 pixels)			
Light source		Laser diodes			
Light output		9,400 lm (Normal) ^{*1} /10,000 lm (Center) ^{*2} / 7,500 lm (Eco) ^{*3} /8,000 lm (Quiet 1) ^{*4} / 6,000 lm (Quiet 2) ^{*5} /3,700 lm (Long Life 1) ^{*6} / 3,100 lm (Long Life 2) ^{*7} /2,500 lm (Long Life 3) ^{*8}	8,500 lm (Normal) ^{*1} /8,800 lm (Center) ^{*2} / 6,800 lm (Eco) ^{*3} /7,200 lm (Quiet 1) ^{*4} / 5,400 lm (Quiet 2) ^{*5} /3,400 lm (Long Life 1) ^{*6} / 2,900 lm (Long Life 2) ^{*7} /2,300 lm (Long Life 3) ^{*8}	7,000 lm (Normal) ^{*1} /7,200 lm (Center) ^{*2} / 5,600 lm (Eco) ^{*3} /2,800 lm (Long Life 1) ^{*4} / 2,300 lm (Long Life 2) ^{*5} /1,900 lm (Long Life 3) ^{*6}	6,000 lm (Normal) ^{*1} /6,200 lm (Center) ^{*2} / 4,800 lm (Eco) ^{*3} /2,400 lm (Long Life 1) ^{*4} / 2,000 lm (Long Life 2) ^{*5} /1,600 lm (Long Life 3) ^{*6}
Time until light output declines to 50 % ^{*3}		20,000 hours (Normal)/Quiet 1/24,000 hours (Eco)/43,800 hours (Long Life 1)/ 61,320 hours (Long Life 2)/87,600 hours (Long Life 3)		20,000 hours (Normal)/24,000 hours (Eco)/43,800 hours (Long Life 1)/ 61,320 hours (Long Life 2)/87,600 hours (Long Life 3)	
Resolution		1920 x 1200 pixels			
Contrast ratio ^{*1}		10,000:1 (Full On/Full Off, Dynamic Contrast [3])			
Screen size (diagonal)		1.27–15.24 m (50–600 in), 1.27–5.08 m (50–200 in) with ET-DLE055, 2.54–8.89 m (100–350 in) with ET-DLE035, 2.54–10.16 m (100–400 in) with ET-DLE020, 16:10 aspect ratio			
Center-to-corner zone ratio ^{*1}		90 %			
Lens		With supplied lens: Powered zoom (throw ratio 1.71–2.41:1), powered focus F 1.7–1.9, f 25.6–35.7 mm Without lens: Optional powered zoom/focus lenses			
Lens shift ^{*4}	Vertical	+50 %, -16 % (+40 %, -16 % with ET-DLE060) (powered)			
	Horizontal	+30 %, -10 % (+10 %, -20 % with ET-DLE020, +19 %, -10 % with ET-DLE060, +28 %, -10 % with ET-DLE105/ET-DLE085) (powered)			
Keystone correction range		Vertical: ±40 ° (±5 ° with ET-DLE020, ±16 ° with ET-DLE060, ±22 ° with ET-DLE105/ET-DLE085/ET-DLE055, +5 ° with ET-DLE035), Horizontal: ±15 ° (±10 ° with ET-DLE060) (cannot be operated with ET-DLE035/ET-DLE020)			
Keystone correction range with optional ET-UK20 Upgrade Kit		Vertical: ±45 ° (±16 ° with ET-DLE060, ±40 ° with ET-DLE150/ET-DLE250/ET-DLE170, ±22 ° with ET-DLE105/ET-DLE085/ET-DLE055), Horizontal: ±40 ° (±10 ° with ET-DLE060, ±15 ° with ET-DLE105/ET-DLE085/ET-DLE055) When [VERTICAL KEYSTONE] and [HORIZONTAL KEYSTONE] are used simultaneously, correction cannot be made exceeding a total of 55 °.			
Terminals	SDI IN	BNC x 1: 3G/HD/SD-SDI input			
	HDMI IN	HDMI 19-pin x 1 (Compatible with HDCP 2.2, Deep Color, 4K/60p signal input ^{*5})			
	DVI-D IN	DVI-D 24-pin x 1 (DVI 1.0 compliant, compatible with HDCP, compatible with single link only)			
	RGB 1 IN	RGB x 1 (BNC x 5): RGB/Y/PaPr/Y/CbCr/YC/VIDEO			
	RGB 2 IN	D-sub HD 15-pin (female) x 1: RGB/Y/PaPr/Y/CbCr			
	SERIAL/MULTI PROJECTOR SYNC IN	D-sub 9-pin (female) x 1 for external control (RS-232C compliant)			
	SERIAL/MULTI PROJECTOR SYNC OUT	D-sub 9-pin (male) x 1 for link control			
	REMOTE 1 IN	M3 x 1 for wired remote control			
	REMOTE 1 OUT	M3 x 1 for link control (for wired remote control)			
	REMOTE 2 IN	D-sub 9-pin (female) x 1 for external control (parallel)			
	DIGITAL LINK	RJ-45 x 1 for network and DIGITAL LINK connections (HDBase™ compliant), PLink™ (Class 2) compatible, 100Base-TX, Art-Net compatible, HDCP 2.2 compatible, Deep Color compatible, 4K/60p signal input ^{*5}			
	LAN	RJ-45 x 1 for network connection, PLink™ (Class 2) compatible, 10Base-T/100Base-TX, Art-Net compatible			
Power supply		AC 100–240 V, 50/60 Hz			
Power consumption		735 W (Normal)/575 W (Eco)/490 W (Quiet 1)/ 365 W (Quiet 2)/265 W (Long Life 1)/ 235 W (Long Life 2)/205 W (Long Life 3)	690 W (Normal)/550 W (Eco)/460 W (Quiet 1)/ 345 W (Quiet 2)/250 W (Long Life 1)/ 225 W (Long Life 2)/200 W (Long Life 3)	545 W (Normal)/435 W (Eco)/ 215 W (Long Life 1)/195 W (Long Life 2)/ 170 W (Long Life 3)	490 W (Normal)/395 W (Eco)/ 200 W (Long Life 1)/180 W (Long Life 2)/ 160 W (Long Life 3)
Operation noise ^{*1}		40 dB (Normal) / 36 dB (Quiet 1) / 35 dB (Quiet 2)		36 dB (Normal)	35 dB (Normal)
Dimensions (W x H x D)		With supplied lens: 498 x 200 ^{*6} x 581 mm (19 19/32" x 7 7/8" x 22 7/8") Without lens: 498 x 200 ^{*6} x 538 mm (19 19/32" x 7 7/8" x 21 3/16")			
Weight ^{*7}		With supplied lens: Approx. 23.0 kg (50.7 lbs) Without lens: Approx. 22.2 kg (48.9 lbs)			
Operating environment		Operating temperature: 0–45 °C (32–113 °F) ^{*8} , operating humidity: 10–80 % (no condensation)			
Applicable software		Logo Transfer Software, Multi Monitoring & Control Software, Early Warning Software, Geometry Manager Pro (ET-UK20 Upgrade Kit, ET-CUK10 Auto Screen Adjustment Kit), Smart Projector Control for iOS/Android™			

^{*1} Measurement, measuring conditions, and method of notation all comply with ISO/IEC 21118: 2020 international standards. Value is average of all products when shipped. ^{*2} Average light-output value of all shipped products measured at center of screen in Normal Mode. ^{*3} Around this time, light output will have decreased by approximately 50 %. IEC62087: 2008 Broadcast Contents, Normal Mode, Dynamic Contrast [3], temperature 30 °C (86 °F), elevation 700 m (2,297 ft) with 0.15 mg/m³ of airborne particulate matter. Panasonic recommends cleaning or checkup at point of purchase after about 20,000 hours. Light-source lifetime may be reduced depending on environmental conditions. Replacement of parts other than the light source may be required in a shorter period. Estimated maintenance time varies depending on environment. ^{*4} Lens shift is not supported on the ET-DLE055, and the optical axis is fixed with the ET-DLE035. ^{*5} 4K signals are converted to the projector's resolution (1920 x 1200 pixels) upon projection. Supported terminals: DIGITAL LINK/HDMI™. ^{*6} With legs at shortest position. ^{*7} Average value. May differ depending on the actual unit. ^{*8} The light output may be reduced to protect the projector depending on the temperature or altitude of operational environment.

Optional Accessories

• Fixed-Focus Lens

ET-DLE035 (0.380:1) / ET-DLE055 (0.785:1)

• Zoom Lens

ET-DLE020 (0.280–0.299:1) / ET-DLE060 (0.600–0.801:1) /
ET-DLE085 (0.782–0.977:1) / ET-DLE105 (0.978–1.32:1) /
ET-DLE150 (1.30–1.89:1) / ET-DLE170^{*} (1.71–2.41:1) /
ET-DLE250 (2.27–3.62:1) / ET-DLE350 (3.58–5.45:1) /
ET-DLE450 (5.36–8.58:1)

^{*} The ET-DLE170 is equivalent of supplied lens. The availability of the ET-DLE170 varies depending on the country.

• Ceiling Mount Bracket

ET-PKD130H (6-axis, for high ceiling)
ET-PKD120H (for high ceiling)
ET-PKD120S (for low ceiling)
Note: Use ET-PKD120H, ET-PKD120S, and
ET-PKD130H in combination with
ET-PKD130B. ET-PKD130H is recommended
when used with ET-DLE035.

• Projector Mount Bracket

ET-PKD130B

• DIGITAL LINK Switcher

ET-YFB200G

Note: ET-YFB200G is not compatible with 4K signals.

• Digital Interface Box

ET-YFB100G

Note: ET-YFB100G is not compatible with 4K signals.

• Geometry Manager Pro Software Upgrade Kit

ET-UK20

• Auto Screen Adjustment Upgrade Kit

ET-CUK10/ET-CUK10P

• Early Warning Software

ET-SWA100 Series

Note: Part number suffix may differ depending on the license type.

^{*} Multi Monitoring & Control Software Ver. 2.0 or later is required.

Please download from the following website:

www.panasonic.net/cns/projector/download/application/

Panasonic®

Weights and dimensions shown are approximate. Specifications and appearance are subject to change without notice. Product availability may vary by country or region. This product may be subject to export control regulations. DLP, DLP logo and DLP Medallion logo are trademarks or registered trademarks of Texas Instruments. The terms HDMI and HDMI High-Definition Multimedia Interface, and the HDMI Logo are trademarks or registered trademarks of HDMI Licensing Administrator, Inc. in the United States and other countries. Trademark PLink is a trademark applied for trademark rights in Japan, the United States of America and other countries and areas. Android is a trademark or registered trademark of Google LLC. IOS is a trademark or registered trademark of Cisco in the U.S. and other countries and is used under license. SOLID SHINE is a trademark of Panasonic Corporation. All other trademarks are the property of their respective trademark owners. © 2020 Panasonic Corporation. All rights reserved.



For more information about Panasonic projectors, please visit:
Projector Global Website – panasonic.net/cns/projector
Facebook – www.facebook.com/panasonicprojectoranddisplay
YouTube – www.youtube.com/user/PanasonicProjector

All information included here is valid as of August 2020.

RZ990Series_G1 Printed in Japan.