



Reduce Shadows, Enhance Flexibility with Eco-Friendly Short-Throw Projection

## PT-VMZ7ST

### Key Features

Stress-free Installation Adapts to Various Layouts

Clear Projection in Bright Spaces

Eco-Friendly Design



## PT-VMZ7ST

<https://eu.connect.panasonic.com/global/en/projectors/pt-vmz7st>

<b>Projector type</b>	LCD projectors
<b>LCD Panel   Pixels</b>	2,304,000 (1920 x 1200) pixels
<b>Light Source</b>	Laser diode
<b>Resolution</b>	WUXGA (1920 x 1200 pixels)
<b>Lens</b>	1.2x manual zoom (throw ratio: 0.797–1.01:1), powered focus, F 1.53–1.66, f 11.3–14.2 mm
<b>Keystone Correction Range</b>	Vertical ±25 %, Horizontal ±35 %
<b>Terminals   HDMI 1/2 IN</b>	HDMI™ 19-pin x 2 (Compatible with HDCP, Deep Color, 4K/30p*7 signal input), CEC supported*8
<b>Power Supply</b>	AC 100 V–240 V, 50/60 Hz
<b>Built in Speaker</b>	10 W monaural
<b>Cabinet Materials</b>	Molded plastic
<b>Operating Environment</b>	Operating temperature: 0–45 °C (32–113 °F)*14, *15, Operating humidity: 20–80 % (no condensation)
<b>Lens shift   Vertical(From the origin point of the lens mounter)</b>	+50%
<b>Center-to-corner zone ratio*2</b>	85 %
<b>Terminals   Audio Out</b>	M3 stereo mini-jack x 1
<b>Filter*12</b>	Included (Estimated maintenance time: approx. 20,000 hours)
<b>Operation Noise*2</b>	37 dB (NORMAL), 37 dB (ECO), 32 dB (QUIET 1), 27 dB (QUIET 2) (TBD)
<b>Weight*13</b>	Approx. 8.4 kg (18.52 lbs) (TBD)