



EX20 Extreme Short throw projector

Need to make a big impression in a small room? Here's the answer!
The EX20 only needs to be half a metre from the wall in order to project a pin-sharp picture 90 cm diagonal in size. Using "Windows Vista® Network" functionality, it can be easily connected to the network over WLAN.
Or plug your USB stick directly into the USB connector and away you go!



BIG PRESENTATIONS IN THE SMALLEST SPACES

The EX20 business projector features a revolutionary innovation called ESP, which stands for 'Extreme Short-throw Projector' so now you can show people the big picture even in the most intimate surroundings.

The EX20 is ideal for corporate, government and educational organisations as it's easily transportable and extremely versatile thanks to a full menu of inputs, outputs and extras.

It's brilliant in other ways too with 2,300 ANSI-lumens of brightness and XGA 1,024x768 display.

The new Brilliant Color™ technology by Texas Instruments and the powerful NCE 4™ chip provide extraordinary lifelike colour and all other technical characteristics are also in a class of their own.

In addition, the EX20 features remote control with laserpointer, password protection and panel lock for ultimate security, digital zoom, and programmable user logo.

KEY BENEFITS

3 year warranty with
90 day replacement warranty
and 90 day lamp warranty

**Windows Vista® Network
(WLAN and LAN)**

Only 4.2 kilograms

Wireless connectivity

Specifications

| | | | |
|---|---|---|---|
| Device 0.55" DMD™ Chip | Lens F = 2.6 - 8.37, manual focus | Outputs - RGB (D-sub 15) - Audio (Stereo Mini Jack) | Extras - Auto Keystone Correction - digital zoom - BrilliantColour™ - Windows Vista™ Network (WLAN & LAN) - USB - password - panellock - user logo - DDC compatible |
| Resolution XGA 1024 x 768 pixels | Digital Keystone Correction auto vertical +/-18° | Other Terminals - RS-232C (D-SUB 9pin) - RJ-45 - USB (Type A) | Accessories - remote control with laserpointer - owners manual (CD ROM) - quick reference - RGB and power-cable - softcase |
| Brightness Standard - 2300lm / ECO - 1800lm | Colour Temperature 6400K +1500K, -1000K | Integrated loudspeaker 1 W (mono) | Options - ceiling mount - spare lamp - camera c001 |
| Contrast 2000 : 1 | Picture size (diagonal) 0.89 - 2.54m | Dimensions (W x H x D) - W/o Protruding Parts 337 x 118 x 265 mm - W/ Protruding Parts 338 x 132 x 267 | |
| Lamp Standard - 275W / Low - 220W | Projection distance - 0.5 - 1.5m - Optical offset 130% | Volume 10.5L | |
| Lamp Life Standard - 2000H / Low - 3000H | Inputs - RGB (2 x D-sub 15) - S-Video (1 x S Terminal) - Composite Video (1 x RCA) - Audio (Stereo Mini Jack) - Video / S-Video Audio (2 x RCA L/R) - Component (Y/PB/PR) - via shared RGB terminal | Weight 4.2 kilogram | |
| Input signals - VGA / SVGA / XGA (True) / WXGA / SXGA / UXGA (Compressed) | | | |
| Video Processor DDP2230 | | | |

Contact Toshiba on: **13 30 70** (Australia)
or visit www.isd.toshiba.com.au/projectors

Toshiba (Australia) Pty. Limited ABN 19 001 320 421. Specifications subject to change without notice. Trademarks as indicated are the property of the respective owners. Toshiba Australia Pty. Limited, Information Systems Division 10/07.