

Key Features

- Advanced LED Light Source | Bright Images in Any Environment |
- Convenient Auto Power On/Off | 360-degree Orientation |
- Comprehensive LAN Control



Product Description

Featuring 1280x800 WXGA resolution and 3,000 ANSI lumens of brightness, the ViewSonic® LS600W is a lamp-free LED projector ideal for business and education. No matter the environment, expect stunning images and vivid colors, as this projector boasts 125% Rec. 709 color accuracy. With 2nd generation LED technology, the LS600W eliminates the need to continuously swap out bulbs and dispose of toxic chemicals. In addition, an IP5X sealed optical engine prevents dust and moisture from entering the projector, ensuring impeccable image quality and a long maintenance-free lifespan of up to 30,000 hours.* An automatic on/off feature delivers efficiency and power savings, while comprehensive LAN control ensures easy management across meeting rooms and classrooms. Whether for business or education, the ViewSonic LS600W LED projector provides a picture-perfect presentation every time.



1. Zoom Ring

2. IR Remote Sensor

3. Control Panel

4. 10W Internal Speaker

5. HDMI 1.4/ HDCP 1.4 (x2)

6. 3.5mm Audio In/Out
7. LAN (RJ45)


8. AC In

9. VGA In


10. USB 2.0 Type A

11. RS232 In

12. Composite RCA Video In




13. Kensington® Lock Slot



1280 x 800
RESOLUTION



3,000 ANSI
LUMENS



1.37-1.64
THROW RATIO



Display:

Type:	DLP LED
Resolution Type:	WXGA (1280x800)
Resolution:	1280 x 800
Brightness (Lumens):	3,000 ANSI
Display Size (in.):	30 - 300 in. / 0.76 - 7.62 m
Throw Distance:	0.86-10.60m (100"@2.95m)
Throw Ratio:	1.37-1.64
Keystone:	Vertical (± 40°) / Horizontal (± 40°)
Lens:	1.2x optical zoom
Light Source (watt):	RGBB LED
Light Source Life, Normal (hours):	30000
Color Depth:	1.07 Billion Colors
Dynamic Contrast Ratio:	3,000,000:1
Aspect Ratio:	16:10

Video Signal:

Frequency Horizontal:	15K~105KHz
Frequency Vertical:	23-120Hz

Compatibility:

PC Resolution (max):	1920 x 1080
Mac® Resolution (max):	1920 x 1080

Connector:

USB 2.0 Type A(1), Ethernet LAN (RJ45)(1), 3.5mm Audio Out(1), 3.5mm Audio In(1), Control (RS232)(1), HDMI 1.4 (with HDCP 1.4)(2), VGA In(1), Composite RCA Video In(1), RCA Audio In (L/R)(1)

Audio:

Internal Speakers:	10W (x1)
--------------------	----------

Power:

Voltage:	100-240V+/- 10%, 50/60Hz AC
Consumption (typical):	270W
Stand-by:	<0.5W

Controls:

Physical Controls:	Keypad, Power key
On Screen Display:	Display, Image, Power Management, Basic, Advanced, System, Information (See user guide for full OSD functionality)

Operating Conditions:

Temperature:	32-104° F (0 - 40° C)
--------------	-----------------------

Additional Hardware:

Kensington Lock Slot:	1
-----------------------	---

Weight (imperial):

Net (lbs):	11.0
Gross (lbs):	15.4

Weight (metric):

Net (kg):	5.0
Gross (kg):	7.0

Dimensions (imperial) (WxHxD):

Physical (in.):	15.2 x 4.6 x 10.9
-----------------	-------------------

Dimensions (metric) (WxHxD):

Physical (mm):	386.0 x 116.0 x 276.0
----------------	-----------------------

General:

Regulations:	cTUVus
PACKAGE CONTENTS:	LS600W projector, power cable, VGA cable, remote control, Quick Start Guide
Warranty:	Three-year limited warranty on parts and labor, 1st year free Express Exchange® service. (One year Express Exchange Service requires product registration).
Recycle/Disposal:	Please dispose of in accordance with local, state or federal laws.
UPC:	766907007145

Accessories:

IFP2410, IFP2710, PGD-350, PJ-SCW-1001W, PJ-WMK-006, PJ-WMK-007, VCB10, VSR100
--

Awards:

