

ViewSonic® PROJECTOR LX720-4K RGB

Key Features

- RGB laser light source delivers lifelike color and consistent brightness
- True 4K HDR with 100% BT.2020 coverage for cinematic detail and depth
- 2,000 ANSI lumens deliver bright, vivid images on screens up to 300 inches
- 1.3x zoom, H/V keystone, four-corner adjustment and warping for flexible installation
- 1 ms input lag and Variable Refresh Rate support keep gameplay smooth and ultra responsive



Product Description

The ViewSonic LX720-4K RGB brings a true cinematic upgrade to your home. Its RGB laser light source covers 100% of the BT.2020 color space, filling every frame with rich and lifelike color. With 2,000 ANSI lumens, true 4K UHD resolution, and HDR/HLG support, movies and games stay bright, sharp, and vivid in any lighting condition. Flexible installation options including 1.3x zoom, side projection, H/V keystone, four-corner, and warping adjustments make it easy to create a large-screen setup that fits perfectly in any room. For gaming, 1 ms input lag and VRR support ensure responsive, fluid performance that keeps every moment smooth and precise.



Visit Us

www.viewsonic.com

SPECIFICATION

Projection System:	0.47" 4K-UHD
Native Resolution:	3840x2160
Brightness:	4800 (RGB Laser Lumens)
Contrast Ratio:	3000000:1
Display Color:	1.07 Billion Colors
Light Source Type:	RGB Laser
Light Source Life (hours) with Normal Mode:	20000
Light Source Life (hours) with SuperEco Mode:	30000 (Eco)
Lens:	F=2.2-2.42, f=11.965-15.54mm
Projection Offset:	110% +/-6%
Throw Ratio:	1.136-1.477
Optical Zoom:	1.3X
Image Size:	60"-300"
Throw Distance:	1.50-9.78m (100"@2.50m)
Keystone:	H: +/-25° , V: +/-25°
Audible Noise (Normal):	33dB
Audible Noise (Eco):	27dB
Input Lag:	1ms
Resolution Support:	VGA(640 x 480) to 4K(3840 x 2160)
HDTV Compatibility:	480i, 480p, 576i, 576p, 720p, 1080i, 1080p, 2160p
Horizontal Frequency:	15K-255KHz
Vertical Scan Rate:	23-240Hz

INPUT

HDMI:	2 (HDMI 2.0, HDCP 2.2)
-------	---------------------------

OUTPUT

Audio-out (3.5mm):	1
Audio-out (HDMI ARC):	1 (share with HDMI Input)
Speaker:	10W Cube
USB Type A (Power):	1 (5V/1.5A)

CONTROL

RS232 (DB 9-pin male):	1
USB Type A (Services):	1 (share with USB A Output)

OTHERS

Power Supply Voltage:	100-240V +/- 10%, 50/60Hz (AC in)
Power Consumption:	Normal: 85W Standby: <0.5W
Operating Temperature:	0~40°C
Carton:	Brown
Net Weight:	3.2kg (7.05 lbs)
Gross Weight:	4.3kg (9.48 lbs)
Dimensions (WxDxH) with Adjustment Foot:	312x234x104mm (12.3x9.2x4.1 in)
Packing Dimensions:	415x168x297mm (16.3x6.6x11.7 in)
OSD Language:	English, French, Spanish, Thai, Korean, German, Italian, Russian, Swedish, Dutch, Polish, Czech, T-Chinese, S-Chinese, Japanese, Turkish, Portuguese, Finnish, Indonesian, Hindi, Arabic, Vietnamese, Greek, Hungarian Total 24 languages
User Guide Language:	English, S-Chinese, T-Chinese, Indonesian, Finnish, French, German, Italian, Japanese, Korean, Polish, Portuguese, Russian, Spanish, Swedish, Turkish, Arabic, Czech, Thai, Vietnamese, total 20 languages

STANDARD ACCESSORY

Power Cord:	1
Remote Control:	1 (w/ backlit)
QSG:	Yes

OPTIONAL ACCESSORY

Wall/Ceiling Mount:	PJ-WMK-007
Carry Bag:	PJ-CASE-008