

Key Features

- 3,500 ANSI Lumens offering bright images in any environment
- Native 1080p Full HD resolution for captivating details
- 1.3x optical zoom & digital lens shift for flexible installation
- True-to-life SuperColor™ Technology



Product **Description**

The ViewSonic PX703HDH is a practical Home Cinema Projector, featuring 3500 ANSI lumens, 1080p Full HD resolution, and ViewSonic's exclusive SuperColor™ technology, which together produce the finest of details and stunning colour in any medium sized space. The projector comes with an energy-saving SuperEco+ mode that reduces power consumption and extends lamp life to up to 20,000 hours, reducing the frequency of lamp replacement and lowering maintenance costs. Digital lens shift and H/V keystone help users easily set up the projector at any angle. Dual HDMI input and USB power supply further increase the flexibility of the user's entertainment experience.



- 1. LED Indicator
- 2. Keypad
- 3. Lens
- 4. Power Key
- 5. Zoom/Focus
- 6. Front IR
- 7. USB Type A



- 8. HDMI
- 9. Audio In/Out
- 10. RS-232
- 11. Kensington Lock

V	F	N	D	n	R

VENDOR				
Vendor:	Qisda			
SPECIFICATION				
Native Resolution:	1920x1080			
DMD Type:	DC3			
Brightness:	3500 (ANSI Lumens)			
Contrast Ratio with SuperEco Mode:	12000:1			
Display Color:	1.07 Billion Colors			
Light Source Type:	Lamp			
Light Source Life (hours) with Normal Mode:	5000			
Light Source Life (hours) with SuperEco Mode:	20000			
Lamp Watt:	203W			
Lens:	F=1.9-2.47, f=12- 15.6mm			
Projection Offset:	110%+/-6%			
Throw Ratio:	1.13-1.47			
Optical Zoom:	1.3x			
Digital Zoom:	0.8x-2.0x			
Image Size:	30"-300"			
Throw Distance:	0.75m- 9.76m(100"@2.5m)			
Keystone:	+/- 40° (V)			
Lens Shift V. Range:	+/- 5% (Digital)			
Audible Noise (Normal):	31dB			
Audible Noise (Eco):	27dB			
Input Lag:	16ms			
Resolution Support:	VGA(640 x 480) to WUXGA_RB(1920 x 1200)*RB-Reduced Blanking			
HDTV Compatibility:	480i, 480p, 576i, 576p, 720p, 1080i, 1080p			
Video Compatibility:	NTSC, PAL, SECAM			
Horizontal Frequency:	15K-102KHz			
Vertical Scan Rate:	23-120Hz			
INPUT				
HDMI:	2 (HDMI 1.4/ HDCP 1.4)			
Audio-in (3.5mm):	1			
OUTPUT				
Audio-out (3.5mm):	1			
Speaker:	10W			
USB Type A (Power):	1 (5V/1.5A)			
CONTROL				
RS232 (DB 9-pin male):	1			

OTHERS				
Power Supply Voltage:	100-240V+/- 10%, 50/60Hz (AC in)			
Power Consumption:	Normal: 300WStandby: <0.5W			
Operating Temperature:	0~40°C			
Carton:	Brown			
Net Weight:	2.62kg			
Gross Weight:	3.78kg			
Dimensions (WxDxH) with Adjustment Foot:	312x222x108mm			
Packing Dimensions:	415x168x297mm			
OSD Language:	English, French, Spanish, Thai, Korean, German, Italian, Russian, Swedish, Dutch, Polish, Czech, T-Chinese, S-Chinese, Japanese, Turkish, Portuguese, Finnish, Indonesian, India, Arabic, Vietnamese, Greek, Total 23 languages			
User Guide Language:	English, S-Chinese, T-Chinese, Indonesian, Finnish, French, German, Italian, Japanese, Korean, Polish, Portuguese, Russian, Spanish, Swedish, Turkish, Arabic, Czech, Thai, Vietnamese, Total 20 languages			
STANDARD ACCESSORY				
Power Cord:	1			
Remote Control:	1			
QSG:	Yes			
Warranty Card:	Yes (CN Only)			
OPTIONAL ACCESSORY				
Lamp/Light Source:	RLC-123			
Wall/Ceiling Mount:	PJ-WMK-007			
Carry Bag:	PJ-CASE-008			

1(share with USB A Output) USB Type A (Services):